

5
(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number
WO 01/13175 A2

(51) International Patent Classification⁷: **G03F**

[KR/KR]; LG Apt. 6-106, Doryong-dong, Youseong-ku, Taejeon-city 305-340 (KR). **HWANG, Yun-Il** [KR/KR]; Kumnamoo Apt. 201-1303, Doonsan-dong, Seo-ku, Taejeon-city 302-736 (KR).

(21) International Application Number: **PCT/KR00/00883**

(22) International Filing Date: 10 August 2000 (10.08.2000)

(25) Filing Language: **English**

(74) Agent: **KIM, Seong-Ki**; 9th Teheran Bd., 825-33, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(26) Publication Language: **English**

(81) Designated States (*national*): JP, US.

(30) Priority Data:
1999/33884 17 August 1999 (17.08.1999) **KR**

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

(71) Applicant (*for all designated States except US*):
LG CHEMICAL LTD. [KR/KR]; LG Twin Tower, Yoido-dong 20, Yongdungpo-ku, Seoul 150-721 (KR).

Published:

— *Without international search report and to be republished upon receipt of that report.*

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **AHN, Yong-Sik** [KR/KR]; Jooho Villa Na-101, 1076-1, Namhyun-dong, Kwanak-ku, Seoul 151-800 (KR). **KIM, Kyung-Jun**

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PHOTOSENSITIVE RESIN COMPOSITION**

(57) Abstract: The present invention relates to a photosensitive resin composition capable of being developed by an alkaline aqueous solution, and provides a photosensitive resin which has superior resolving power by having a chemical bond between a binder resin and a crosslinking compound as well as a chemical bond between binder resin chains at an exposed area during an exposure process, thus maximizing a solubility difference between an exposed area and a non-exposed area during a developing process, and which has process benefits as well as superior film characteristics by reducing a consumed amount of a crosslinking compound, thus minimizing total amount of UV irradiation necessary.

WO 01/13175 A2

Pub. No. WO 01/13175 A2